

# Mini digital indicators

# S\_Dial S233

## TECHNICAL SPECIFICATIONS

		905.4140	905.4540	905.4511	905.4515
Measuring range	mm	5	5	5	5
Display 90°		●	●	---	---
Analog scale		---	---	●	●
Resolution	mm	0.01	0.001	0.001	0.001
Execution <sup>3)</sup>		S	S	S	P
Max. Error fe	µm	10 <sup>1)</sup>	5	4	4
Repeatability	µm	2	2	2	2
Measuring force	N	0.50 - 0.65 <sup>2)</sup>	0.50 - 0.65 <sup>2)</sup>	0.50 - 0.65 <sup>2)</sup>	0.60 - 1.20 <sup>2)</sup>
Zero setting		●	●	●	●
REL and ABS measurement		●	●	---	---
Resolution selection		---	●	●	●
PRESET = (max. 130 mm)		●	●	---	---
Min / max / delta display		---	---	●	●
Selection of measuring direction		●	●	---	---
S_Connect : Power	USB / RS232 / Wireless <sup>4)</sup>				
IP rating	IP65				

		905.4121	905.4125	905.4521	905.4525	905.4527
Measuring range	mm	12.5	12.5	12.5	12.5	12.5
Analog scale		---	---	---	---	---
Resolution	mm	0.01	0.01	0.001	0.001	0.001
Execution <sup>3)</sup>		S	P	S	P	S
Max. Error fe	µm	10 <sup>1)</sup>	10 <sup>1)</sup>	5	5	5
Repeatability	µm	2	2	2	2	2
Measuring force	N	0.5 - 0.90 N	0.6 - 1.3 N	0.5 - 0.90 N	0.6 - 1.3 N	0.5 - 0.90 N
Zero setting				●		
REL and ABS measurement				●		
Resolution selection		---	---	●	●	●
PRESET = (max. 130 mm)				●		
Min / max / delta display				---		
Selection of measuring direction				●		
Multiplication factor				---		●
S_Connect : Power	USB / RS232 / Wireless <sup>4)</sup>					
IP rating	IP65					

<sup>1)</sup> ± 1 digit

<sup>2)</sup> Values ± 20%, indicator in vertical position, outgoing measuring spindle

<sup>3)</sup> S = Standard P = Protected

<sup>4)</sup> see cables chapter