



More information on the website
radwag.com/en/info,w1,Z29

MA 110.X2.A Moisture Analyzer



The drawings, photos and graphics used are for illustrative purposes only.

Functions

 Autotest	 Dosing	 Percent Weighing	 Parts counting
 Peak hold	 Formulation	 Newton unit measurement	 Statistics
 Checkweighing	 IR sensors	 Under-pan weighing	 GLP Procedures
 Animal weighing	 Density determination	 Ambient conditions monitoring	 Replaceable unit
 Statistical Quality Control	 ALIBI Memory	 Drying modes	 Samples drying
 Moisture content analysis	 Dry mass determination	 Mass for titrator	 Wi-Fi

Datasheet

Metrological parameters	
Maximum capacity [Max]	110 g
Readability [d]	1 mg

Metrological parameters	
Tare range	-110 g
Adjustment	external
Maximum sample weight	110 g
Heating module	IR emitter
Moisture content repeatability	+/-0,05% (sample ~ 2g), +/-0,01% (sample ~ 10g)
Moisture content readability	0,001%
Drying temperature range	max 160 °C
Physical parameters	
Leveling system	manual
Display	5" graphic color touchscreen
Protection class	IP 43
Weighing pan dimensions	ø90, h= 8 mm
Packaging dimensions	470×380×336 mm
Net weight	5,2 kg
Gross weight	6,7 kg
Communication interface	
Communication interface	RS232 ¹ , USB-A, USB-B, Ethernet, Wi-Fi
Electrical parameters	
Power supply	100V – 120V AC 50/60Hz or 200V-240V AC 50/60Hz
Power consumption	6 W
Heating module power	450 W
Environmental conditions	
Operating temperature	+10 ÷ +40 °C
Features of use	
Drying method	4 drying profiles (standard, fast, step, mild)
Finish mode	4 modes (automatic, manual, time-defined, user-defined)
Additional functions	sample traceability
Maximum sample height	20 mm

1 Barcode scanners, available as weighing instrument accessory, communicate with the instrument via RS232 interface exclusively.

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Accessories

Barcode scanners
Protective cover for balances
Moisture analyzer accessories
Balance Storage Case

Antivibration Tables
Water Vapour Permeability Determination Set
RS 232, RS 485 cables
RS 232 cables (scale - printer)

Software

RAD-KEY
E2R System
RADWAG Development Studio

LabVIEW Driver
Alibi Reader

Device dimensions

