KERN MBC 15K2DM



Elegantly-shaped baby scale – with approval for professional mobile or stationary medical use in medical diagnostics, verification optional



Category	
Brand	KERN
Product categoriy	Medical scale
Product group	Baby scale
Product family	MBC

Multi-range balance
Strain gauge
6 kg; 15 kg
0,002 kg; 0,005 kg
3.000, 3.000
± 0,002 kg; 0,005 kg
0,002 kg; 0,005 kg
6 kg; 14,995 kg
kg
kg
kg
0,04 kg; 0,1 kg
Adjusting with external weight
15 kg (M1)
3 s
10 min; 10 min
0,002 kg

Approval	
CE mark	✓
Accuracy classe	III
Verification scale interval [e]	0,002 kg; 0,005 kg
Conformity assessment possible ex works	/
Approval according to 93/42/EEC (med.)	✓

Display	
Display type	LCD
Display backlight	✓
Display digit height	25 mm
Languages of the user interface	Symbol language

Construction	
Dimension display device (W×D×H)	200×130×60 mm
Dimension housing (W×D×H)	320×410×70 mm
Dimensions weighing platform (W×D×H)	600×280×55 mm
Dimensions completely mounted (W×D×H)	600×410×112 mm
Material display housing	Plastics
Material housing	plastic
Material weighing plate	plastic
Material platform	Plastics
Dimensions weighing surface (W×D)	600×276 mm
Transport safety lock - bolt torque	0,1 Nm

Functions	
Number of keys for operation	6
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min 5 min 30 min 15 min
Tare function	manual (single & multi)
Hold function	✓
Function for averaging under unstable weighing conditions	✓

Power Supply	
Input voltage power supply / power [Max]	100 V - 240 V, 50 / 60 Hz
Input voltage device / power [Max]	12 V, 500 mA
Plug-in power supply type	Power adapter
Supplied power supply	Power supply & battery function (battery not included)
Plug-in power supply / adapter for countries - included with the delivery	EURO UK CH
Plug-in power supply / adapter for countries - optional	EURO AUS UK US CH

1

KERN MBC 15K2DM



Elegantly-shaped baby scale – with approval for professional mobile or stationary medical use in medical diagnostics, verification optional

Rechargeable battery optional	Rchrg. battery optional - intern
Rechargeable battery charging time	12 h
Rechargeable battery operating time - backlight on	20 h
Rechargeable battery operating time - backlight off	40 h
Battery	6×1.5 V AA
Battery / accumulator type	Alkali(-Manganese)
Battery connection	Battery insert
Battery operating time	20 h

Environmental conditions	
Humity of environment [Max]	80 %
Ambient temperature [Min]	-10 °C
Ambient temperature [Max]	40 °C
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

Packing & Shipping	
Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	480×654×177 mm
Net weight	4,405 kg
Shipping method	Parcel service
Net weight approx.	4,6 kg
Gross weight approx.	6 kg
Shipping weight	11,1 kg

Services (optional)	
Article number for adjustment at the location of installation	961-248
Article number for conformity assessment	965-128.
Article number for DAkkS calibration	963-128
Article number for certificate of conformity (verification)	969-517

Pictograms
STANDARD
MOVE BATT A LL 1 DAY
OPTION
ACCU +3 DAYS



FACTORY